



General Characteristics

Dimension solar shingles:	745 mm x 745 mm x 7.5 mm
Front glass:	3.2 mm thermally tempered solar glass with textured surface
Back glass:	3.2 mm heat-strengthened float glass
Junction box:	According to IEC 62790
Bypass diodes:	2 diodes
Connection cable:	Solar cable 4 mm ² , 950 mm length
Connector:	Original Stäubli MC4-Evo2
System weight:	Standard 20.5 kg/m ² , Alpin 25.0 kg/m ²
Substructure:	Wooden slats with M6 inlets
Tested temperature range:	-40°C until +85°C
Product guarantee:	12 years
Performance guarantee:	10 years at 90 % of the nominal output 30 years at 80 % of the nominal output

Quality and Warranty

IEC certificate:	IEC 61730, IEC 61215*
Fire safety:	DIN-EN 13501-5: B _{ROOF} (t1) DIN 4102-7: class B1
Hail resistance class:	HW 4
Permissible loads:	Snow load**: with alpine battens: +3,600 Pa +5,400 Pa +8,500 Pa +12,750 Pa Wind load***: with wind hooks: ±2,400 Pa ±3,600 Pa ±3,600 Pa ±5,400 Pa (design load test load)
Accessibility:	Dry roof accessible without warranty restrictions
Water resistance:	Minimum roof pitch of 4° (see information sheet: sub-roof requirements)
System performance:	Up to 155 W _p /m ²

*in progress **Snow load pressure only (+) *** Wind load pressure and suction (±)

System Properties

Maximum System voltage (IEC)	1000 V DC
Reverse current overload	18 A

Temperature Coefficients

Temperature coefficients α	for I _{sc}	+0.07 %/K
Temperature coefficients β	for U _{oc}	-0.36 %/K
Temperature coefficients γ	for P _{mpp}	-0.38 %/K

Electrical Properties *

Type of solar tile	Solar tile	Solar tile bottom	Solar tile top	Solar tile left/right
Nominal output**	76 W _p	45 W _p	50 W _p	30 W _p
Voltage U _{mpp}	8.1 V	4.8 V	5.3 V	3.2 V
Current I _{MPP}	9.4 A	9.4 A	9.4 A	9.4 A
Open circuit voltage U _{oc}	10.2 V	6.1 V	6.8 V	4.1 V
Short circuit current I _{sc}	9.5 A	9.5 A	9.5 A	9.5 A

*under standard test conditions (1000 W/m², 25°C and AM 1.5) ** Tolerance Nominal power ± 3%

System Enhancements

Fixed supplementary tiles:	SunStyle®-Tile (VSG, grey)
Supplementary tiles cut to size:	SunStyle®-Aluminium composite (grey)

Snow and wind hook:	Stainless steel, black, 4mm INOX
Alpine support battens:	> 3600 Pa